



China 608zz Bearing Supplier



6200 to 6215 - O&Kai Z1V1 Z2V2 Z3V3 Deep Groove Ball Bearing SKF NSK NTN NACHI Koyo FAG OEM

Bearing No. 6200

6200 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 10x30x9 mm |
| Bore Diameter | 10 mm |
| Outer Diameter | 30 mm |
| Width | 9 mm |
| d | 10 mm |
| D | 30 mm |
| B | 9 mm |
| C | 9 mm |
| r min. | 0.6 mm |
| da min. | 15 mm |
| Da max. | 25 mm |
| ra max. | 0.6 mm |
| Weight | 0.032 Kg |
| Basic dynamic load rating (C) | 5,1 kN |
| Basic static load rating (C0) | 2,39 kN |
| (Grease) Lubrication Speed | 24000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |



China 608zz Bearing Supplier

| | |
|---------------------------------|--|
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 10MM Bore; 30MM Outside Diameter; 9MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Weight / LBS | 0.06834 |
| Outer Race Width | 0.354 Inch 9 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore | 0.394 Inch 10 Millimeter |
| Outside Diameter | 1.181 Inch 30 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 10 mm |
| Width | 9 mm |
| Fillet Radius/Chamfer | 0.6 mm |
| | |



China 608zz Bearing Supplier

| | |
|-------------------------|-------------------|
| Dynamic Load Rating | 5,100 N |
| Static Load Rating | 2,390 N |
| Limiting Speed - Grease | 25,000 rpm |
| Limiting Speed - Oil | 30,000 rpm |
| Factor f_0 | 13.2 |
| Radial Clearance | 0.002 to 0.013 mm |
| da (min) | 15 mm |
| Da (max) | 25 mm |
| ra (max) | 0.6 mm |