



## China 608zz Bearing Supplier



6204 Bearing 2D drawings and 3D CAD models

### 6204 SKF Motorcycle Deep Groove Ball Bearings

Bearing No. 6204

Size	47x20x14 mm
Bore Diameter	47 mm
Outer Diameter	20 mm
Width	14 mm
d	20 mm
D	47 mm
B	14 mm
d <sub>1</sub>	28.8 mm
D <sub>2</sub>	40.59 mm
r <sub>1,2</sub> - min.	1 mm
d <sub>a</sub> - min.	25.6 mm
D <sub>a</sub> - max.	41.4 mm
r <sub>a</sub> - max.	1 mm
Basic dynamic load rating - C	13.5 kN
Basic static load rating - C <sub>0</sub>	6.6 kN
Fatigue load limit - P <sub>u</sub>	0.28 kN
Reference speed	32000 r/min
Limiting speed	20000 r/min
Calculation factor - k <sub>r</sub>	0.025
Calculation factor - f <sub>0</sub>	13
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



## China 608zz Bearing Supplier

Weight / Kilogram	0.109
EAN	7316577061645
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	6204
Weight / LBS	0.24
Outside Diameter	1.85 Inch   47 Millimeter
Outer Race Width	0.551 Inch   14 Millimeter
Bore	0.787 Inch   20 Millimeter
d <sub>1</sub>	28.8 mm
D <sub>2</sub>	40.59 mm
r <sub>1,2</sub> min.	1 mm



## China 608zz Bearing Supplier

$d_a$ min.	25.6 mm
$D_a$ max.	41.4 mm
$r_a$ max.	1 mm
Basic dynamic load rating C	13.5 kN
Basic static load rating $C_0$	6.55 kN
Fatigue load limit $P_u$	0.28 kN
Calculation factor $k_r$	0.025
Calculation factor $f_0$	13
Mass bearing	0.1 kg